BEHR PREMIUM PLUS®
Ceiling Paint

- Acrylic Latex
- Excellent Hiding
- Spatter Resistant

IMPORTANT! DO NOT OPEN CAN WITHOUT READING INSTRUCTIONS.
PROTECT FROM FREEZING.

WHERE TO USE

- Primed or painted Interior Ceilings.

PREPARATION†

- Remove loose paint, wash off any dirt and grease with detergent, remove mildew stains with a mildew stain removing product.
- Scuff sand glossy surfaces.
- Countersink nailheads, repair imperfections and sand smooth.
- Remove all dust with a damp cloth, allow to dry.
- Allow new stucco, plaster and masonry to cure for 30 days before priming.

PRIME

- Use a product such as BEHR ENAMEL UNDERCOATER PRIMER & SEALER NO. 75. On new drywall in low-moisture rooms, use a product such as BEHR DRYWALL PRIMER & SEALER NO. 73.

APPLICATION

- Use product when the surface and air temperatures are between 50-90°F (10-32°C).
- Stir paint occasionally. Intermix containers of same product to ensure color and sheen uniformity.
- Use a high quality 3/8-1/2" nap roller cover, nylon/polyester brush or an airless sprayer (.015" - .019" spray tip, 60 mesh filter).
- Coverage is 250-400 sq. ft. (23-37 m^2) per gallon depending on the surface texture, porosity and application method.
- Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 1/2 pint per gallon.
- Certain colors may require more than one coat for complete hide
- Popcorn style acoustic ceilings; use acoustic ceiling roller cover or airless sprayer (.015" - .019" spray tip, 60 mesh filter).

WARRANTY

- Visit www.Behr.com for complete warranty information.

DRY TIME

- Dries to touch in 2 hours at 77°F (25°C) and 50% humidity, re-coat in 4 hours. Longer dry time required in cooler temperatures and in higher humidity.
- After 4 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent.

CLEAN-UP

- Use soap and water.
- Properly dispose of all soiled rags and protect unused **product from freezing**.
- To recycle or properly dispose of paint in your community, contact your local household refuse collections service.

Refer to the BEHR Interior Paint Guide for additional tips or visit us at behr.com for expert project advice and perfect color coordination with COLORSMART BY BEHR™.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH-approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

To consult with a BEHR Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2011 BEHR PROCESS CORPORATION
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <50 g/L • REV. 05/11